


Parts No. :No.1,No.2
Coating :NAYLON 11



4 SIZE:40A~50A

5	Gasket	Non-Asbestos	ガスケット	Non-Asbestos	1
4	Plug	Stainless Steel	プラグ	SUS304	1
3	Screen	Stainless Steel	スクリーン	SUS304	1
2	Cap	Ductile Cast Iron	キャップ	FCD450	1
1	Body	Ductile Cast Iron	本体	FCD450	1
	Name of Parts	Material	部品名	材質	Q.TY

Size	L	H1	d	Screen		Flange JIS 10K FF				Plug	Weight (kg)
				ds	ls	D	C	t	n-h		
15A	130	61	15	22	40	95	70	16	4-15		1.9
20A	140	75	20	27	56	100	75	18	4-15		2.5
25A	160	88	25	34	66	125	90	18	4-19		4.0
32A	175	104	35	43	76	135	100	20	4-19		5.2
40A	190	115	40	50	85	140	105	20	4-19	R 1/2	6.7
50A	225	140	50	61	107	155	120	20	4-19	R 1/2	10.2

* フランジ厚みは規格より厚くなっております。
* Thickness of Flange thicker than standard type

Specification	
Fluid	
Press.	MPa
Temp.	
Flow Rate	
Inside Screen	Mesh
Outside Screen	- ㌢/cm ²

TYPE SY-40C STRAINER
ストレーナ

Approval	T. Nishiyama
Check	N. Yabutani
Drawing	T. Tsubuku
Drawing No.	Yz-0958-2105
Date	29 AUG.2005

