



5	Plug	Stainless Steel or Cast Stainless Steel	プラグ	SUS or SCS	1
4	Screen	Stainless Steel	スクリーン	SUS304	1
3	Gasket	PTFE	ガスケット	PTFE	1
2	Cap	Bronze	キャップ	CAC406	1
1	Body	Bronze	本体	CAC406	1
No.	Name of Parts	Material	部品名	材質	Q. TY

Size	d	L	H <sub>1</sub>	l <sub>s</sub>	d <sub>s</sub>	⑤ Plug	Weight (kg)
15A	Rc 1/2	86	55	35	20	—	0.5
20A	Rc 3/4	98	70	50	25	—	0.8
25A	Rc 1	117	80	60	32	—	1.1
32A	Rc 1 1/4	145	92	70	40	—	1.9
40A	Rc 1 1/2	148	105	75	45	R 3/8	2.6
50A	Rc 2	178	122	90	56	R 3/8	3.8

Specification		
Fluid		
Press.	MPa	
Temp.	℃	
Flow Rate		
Inside Screen	Mesh	
Outside Screen	∅	ヶ/cm <sup>2</sup>

TYPE SY-6 STRAINER  
ストレーナ

Approval	H. Iwamoto
Check	H. Kamada
Drawing	K. Takenaka
Drawing No.	Y-462-1401-1B
Date	24 APR. 2017

